



## SSC80A4GS6

### N-Channel Enhancement Mode MOSFET

#### ➤ Features

$V_{DS}$	$V_{GS}$	$R_{DS(ON)}$ Typ.	$I_D$
100V	$\pm 20V$	240m $\Omega$ @10V	2.2A
		260m $\Omega$ @4V5	

#### ➤ Description

This device uses advanced trench technology to provide excellent R<sub>DS(ON)</sub> and low gate charge. This device is suitable for use as a load switch or in PWM applications.


#### ➤ Applications

- Intelligent Lighting
- Load Switch
- Portable Devices
- DCDC Conversion


#### ➤ Ordering Information

Device	Package	Shipping
SSC80A4GS6	SOT-23	3000/Reel


#### ➤ Pin configuration



**SOT-23**



**Pin Configuration (Top View)**



**Marking**



➤ **Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)**

Symbol	Parameter	Ratings	Unit
$V_{DSS}$	Drain-to-Source Voltage	100	V
$V_{GSS}$	Gate-to-Source Voltage	$\pm 20$	V
$I_D$	Continuous Drain Current <sup>a</sup>	2.2	A
$I_{DM}$	Pulsed Drain Current <sup>b</sup>	8.8	A
$P_D$	Power Dissipation <sup>c</sup>	1.76	W
$T_J$	Operation junction temperature	-55~150	$^{\circ}\text{C}$
$T_{STG}$	Storage temperature range	-55~150	$^{\circ}\text{C}$

➤ **Thermal Resistance Ratings ( $T_A=25^{\circ}\text{C}$  unless otherwise noted)**

Symbol	Parameter	Maximum	Unit
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance <sup>a</sup>	71	$^{\circ}\text{C}/\text{W}$

Note:

- The value of  $R_{\theta JA}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz.copper, in a still air environment with  $T_A=25^{\circ}\text{C}$ . The value in any given application depends on the user is specific board design. The power dissipation is based on the  $t \leq 10\text{s}$  thermal resistance rating.
- Repetitive rating, pulse width limited by junction temperature.
- The power dissipation  $P_D$  is based on  $T_{J(MAX)}=150^{\circ}\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heat sinking is used.




➤ **Electrical Characteristics (T<sub>A</sub>=25°C unless otherwise noted)**


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	100			V
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250uA	1	1.5	2.5	V
Drain-Source On-Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 1A		240	300	mΩ
		V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 0.5A		260	330	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 100V, V <sub>GS</sub> = 0V			1	μA
Gate-Source Leak Current	I <sub>GSS</sub>	V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V			±100	nA
Forward Voltage	V <sub>SD</sub>	V <sub>GS</sub> = 0V, I <sub>S</sub> = 1A			1.3	V
Input Capacitance	C <sub>ISS</sub>	V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V, f = 1MHz		320		pF
Output Capacitance	C <sub>OSS</sub>			20		
Reverse Transfer Capacitance	C <sub>RSS</sub>			14		
Turn-on Delay Time	T <sub>D(ON)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 1A, V <sub>DS</sub> = 30V, R <sub>G</sub> = 3Ω		14		ns
Rise Time	T <sub>r</sub>			53		
Turn-off Delay Time	T <sub>D(OFF)</sub>			17		
Fall Time	T <sub>f</sub>			11		
Total Gate Charge	Q <sub>G</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 30V, I <sub>D</sub> = 2A		5.2		nC
Gate to Source Charge	Q <sub>GS</sub>			1.2		
Gate to Drain Charge	Q <sub>GD</sub>			1.6		




➤ **Typical Performance Characteristics ( $T_A=25^\circ\text{C}$  unless otherwise noted)**




**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current and Gate Voltage**



**On-Resistance vs. Gate-to-Source Voltage**




**On-Resistance vs. Junction Temperature**




**Safe Operating Area vs. Junction-to-Ambient**

## ➤ Package Information



## ➤ Recommended Pad outline





## DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.