

**SSC1N4448N1**

SSC1N4448N1

Fast Switching Diode

● Features


- ◊ Fast Switching Speed
- ◊ Ultra-Small Surface Mount Package
- ◊ Low Reverse Leakage Current
- ◊ Ideal for Battery Powered Portable Applications
- ◊ RoHS Compliant/Green EMC

● PIN configuration

DFN1006-2L(Bottom View)Circuit Diagram

● Applications

- ◊ High speed switching for detection
- ◊ Battery Powered Portable
- ◊ Mobile phone, Note book PC

Marking(Top View)


● Absolute maximum rating @ $T_A=25^\circ C$

Parameter	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Repetitive Peak Reverse Voltage	V_{RRM}		
Working Peak Reverse Voltage	V_{RWM}	80	V
Reverse Voltage(DC)	V_R		
Forward Continuous Current	I_{FM}	300	mA
Average Rectified Forward Current	I_o	150	mA
Non-Repetitive Peak Forward Surge Current@ t=8.3ms	I_{FSM}	1	A
Power Dissipation	P_D	150	mW
Operating Temperature	T_J	-55 ~ +150	°C
Storage Temperature	T_{STG}	-55 ~ +150	°C


- **Electrical Characteristics @ $T_A=25^\circ\text{C}$**

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Reverse Voltage	V_R	$I_R = 100\mu\text{A}$	80			V
Forward Voltage	V_F	$I_F = 5\text{mA}$			0.7	V
		$I_F = 10\text{mA}$			0.8	
		$I_F = 100\text{mA}$			1.0	
		$I_F = 150\text{mA}$			1.2	
Reverse Current	I_R	$V_R = 20\text{V}$			25	nA
		$V_R = 80\text{V}$			1	μA
Total Capacitance	C_T	$V_R = 0, f = 1\text{MHz}$			3	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=10\text{mA}, I_{rr}=0.1 \times I_R$			4	ns


- **Typical Performance Characteristics**




Forward Voltage vs. Forward Current



Reverse Voltage vs. Reverse Current



Power Derating vs. Ambient Temperature



Total Capacitance vs. Reverse Voltage

- Package Information**


Ordering Information

Device	Package	Marking	Qty per Reel	Reel Size
SSC1N4448N1	DFN1006-2L	T8	10000	7 Inch


Mechanical Data

Case: DFN1006-2L

Case Material: Molded Plastic. UL Flammability



DIM	Millimeters	
	Min	Max
A	0.45	0.55
A1	0.00	0.05
D	0.55	0.65
E	0.95	1.05
b	0.45	0.60
e	0.65TYP	
L	0.2	0.3
L1	0.05REF	

Recommended Pad outline


Unit:mm

**DISCLAIMER**

AFSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. AFSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G., OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.