



SSCN84XGS6

NPN Switching Transistor

➤ Description

This product is general usage and suitable for many different applications. It can be used for medium power amplifiers and switches requiring collector currents up to 100 mA.


➤ Features

- Ideally suited for automatic insertion
- For Switching and AF Amplifier Applications


➤ Ordering Information

| Device | Marking | Package | Shipping |
|-------------|---------|---------|-----------|
| SSCN846AGS6 | 1A | SOT-23 | 3000/Reel |
| SSCN846BGS6 | 1B | | |
| SSCN847AGS6 | 1E | | |
| SSCN847BGS6 | 1F | | |
| SSCN847CGS6 | 1G | | |
| SSCN848AGS6 | 1J | | |
| SSCN848BGS6 | 1K | | |
| SSCN848CGS6 | 1L | | |


➤ Pin configuration



SOT-23



Circuit Diagram



Marking (Top View)



➤ **Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise noted)**









| Parameter | Symbol | Value | Unit |
|---------------------------------------------|-----------------|------------|---------------------------|
| Collector-Base Voltage | 846 | 80 | V |
| | 847 | 50 | |
| | 848 | 30 | |
| Collector- Emitter Voltage | 846 | 65 | V |
| | 847 | 45 | |
| | 848 | 30 | |
| Emitter-Base Voltage | V_{EBO} | 6 | V |
| Collector Current-Continuous | I_C | 100 | mA |
| Collector Power Dissipation | P_C | 200 | mW |
| Thermal Resistance From Junction To Ambient | $R_{\theta JA}$ | 625 | $^\circ\text{C}/\text{W}$ |
| Junction Temperature | T_J | 150 | $^\circ\text{C}$ |
| Storage Temperature | T_{STG} | -55 to 150 | $^\circ\text{C}$ |

➤ **Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)**

| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
|--------------------------------------|------------------|----------------------------------------------------------|----------------------------|------|------|---------------|
| Collector-Base Breakdown Voltage | 846 | $I_C=10\mu\text{A}, I_E=0$ | 80 | | | V |
| | 847 | | 50 | | | |
| | 848 | | 30 | | | |
| Collector-emitter Breakdown Voltage | 846 | $I_C=10\text{mA}, I_B=0$ | 65 | | | V |
| | 847 | | 45 | | | |
| | 848 | | 30 | | | |
| Emitter -Base Breakdown Voltage | BV_{EBO} | $I_E=10\mu\text{A}, I_C=0$ | 6 | | | V |
| Collector Cutoff Current | 846 | $V_{CB}=70\text{V}, I_E=0$ | | | 0.1 | μA |
| | 847 | | $V_{CB}=50\text{V}, I_E=0$ | | | |
| | 848 | | $V_{CB}=30\text{V}, I_E=0$ | | | |
| Emitter Cutoff Current | I_{EBO} | $V_{EB}=5\text{V}, I_C=0$ | | | 100 | nA |
| DC Current Gain | 846A, 847A, 848A | $V_{CE}=5\text{V}, I_C=2\text{mA}$ | 110 | | 220 | |
| | 846B, 847B, 848B | | 200 | | 450 | |
| | 847C, 848C | | 420 | | 800 | |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | $I_C=100\text{mA}, I_B=5\text{mA}$ | | | 0.5 | V |
| Base-Emitter Saturation Voltage | $V_{BE(sat)}$ | $I_C=100\text{mA}, I_B=5\text{mA}$ | | | 1.1 | V |
| Collector Capacitance | C_{ob} | $V_{CB}=10\text{V}, f=1\text{MHz}$ | | | 4.5 | pF |
| Transition frequency | f_T | $V_{CE}=5\text{V}, I_C=10\text{mA}$ $f=100\text{MHz}$ | 100 | | | MHz |





➤ Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)




➤ Package Information

SOT-23



| DIM | Millimeters | | |
|----------|-------------|------|------|
| | Min. | Typ. | Max. |
| A | 0.89 | - | 1.12 |
| A1 | 0.01 | - | 0.10 |
| A2 | 0.88 | 0.95 | 1.02 |
| b | 0.30 | - | 0.51 |
| c | 0.08 | - | 0.18 |
| D | 2.80 | 2.90 | 3.04 |
| E | 2.10 | 2.37 | 2.64 |
| E1 | 1.20 | 1.30 | 1.40 |
| e | 0.95 | | |
| e1 | 1.90 | | |
| L | 0.40 | 0.50 | 0.60 |
| L1 | 0.55 | | |
| N | 3 | | |
| θ | 0° | - | 8° |

Recommended Pad outline (Unit: mm)





DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICIENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.